



## Selective Laser Sintering Technology



### PRODUCTIVE

32 liters build volume  
Up to 2 liters/hour build rate



### ACCURATE

450µm laser beam size  
Advanced realtime slicer



### FLEXIBLE






Easy to switch between  
materials



## Prodways Selective Laser Sintering Printer The industrial SLS® revolution

The ProMaker P1000 X provides **industrial capabilities for Additive Manufacturing prototyping and production**. This versatile 3D printer meets the needs of a wide range of industries such as aerospace, automotive, healthcare, design and architecture.

### SPECIFICATIONS

	Build chamber size (LxWxH)	300 x 300 x 360 mm   11.8 x 11.8 x 14.2 in
	Build rate @0.1mm layer thickness*	2 liters/hour
	Scanning speed	8 m/s   315 in/s
	Focusing system	F-Theta Lens
	Laser power and type	60W CO2 - 450 µm spot size
	Layer thickness*	60/100/120 µm
	Powder feed type	Bi-directional, hot feed cylinders system. Counter-rotating roller recoater
	Max chamber temperature	200 °C   392 °F
	Thermal field control	24 x 24 points grid system
	Heating system	10 independent IR heaters
	Camera system	Integrated video camera
	Software features	In-machine realtime slicer, compatible with STL and 3MF file formats
	Available materials	PA12, PA11 natural and glass filled, TPU, PP
	Printer size (LxWxH)	1700 x 1159 x 2008 mm   67 x 46 x 79 in
	Nitrogen supply	Integrated high purity nitrogen generator
	Weight	750 Kg   1653 lbs.
	Power requirements	210 – 240 VAC, 32A, 50/60 Hz

\* Depending on material, geometry and nesting density

### Address

上海锦廷机电科技有限公司  
上海市青浦区盈港东路6433号C2-113  
官网：www.gyrotec.com.cn

### Hotline

座机：021-63233656  
手机：189-6470-4171  
邮箱：info@gyrotec.com.cn

